

EIS- 4G LCD 200

GSM Door Entry Unit



FEATURES

- Simple installation and setup
- Back lit for easy visibility
- Up to 200 apartments *(by model)
- 2 phone numbers per apartment
- Easy access: Up to 1000 additional caller ID numbers and 2000 (4 digit) PIN codes
- 2 relay outputs / 2 alarm inputs
- Up to 20,000 log events
- Supports 4G-GSM wireless carrier



SPECIFICATIONS

Mounting	Post or Surface
Format	Wiegand 26-bit input / output
Power supply	14.4/24 VDC 12-16 VAC
Current Consumption	
Transmitting Mode	330mA / 14 VDC
Idle Mode	360mA / 14VDC
Unit Dimensions	11-7/16 x 4-7/16 x 2-3/16"
External Patch Antenna SMA	1
Front Plate	Grade 304 Stainless steel
Lockable Housing	Powder coated

ACCESSORIES

EISWARE Programming Software

Available on IOS or Android App and online at www.eisware.com.

Search:
EISWARE WEB



Optional receiver and transmitter module for wireless application



Contact us for Details

PJL & Associates
626.488.2478
www.pjlprofessionalservices.com



All items are trademarks of their respective holders.

To have your fax number removed from future specials, please call Removal Services - 800-915-2571 ext. 47540 or fax to 866-975-0404.